

DECLARATION OF PERFORMANCE

N° 040007-CPR2013-IT

(1/2)

1. Unique identification code of the product-type:

**X-FOAM WAFER
Extruded polystyrene panels (XPS)**

2. Intended use of the product:

Thermal insulation for buildings according to EN 13164

3. Name and contact address of the manufacture:

**EDILTEC Bayern GmbH
Ottostr. 5
D 92442 WACKERSDORF
Phone 211/125/20802 – Ust-ID-Nr.: DE258227256**

4. System of assessment and verification of constancy of performance:

System 3

5. Notified body:

**FIW – FORSCHUNGSINSTITUT FÜR WÄRMESCHUTZ e.V. Manchen Lochhamer Schlag
4 -82166 Gräfelfing****Notified testing laboratory (NB 0751) carried out determination of the product type (ITT) for groups of products according to characteristic.**

❖ The performance of the product identified in point 1 is in conformity with the declared performance in Annex

❖ This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3

Wackersdorf 11/02/2021

The legal representative: Ing. Stefano Sboarina



ANNEX DECLARATION OF PERFORMANCE

N° 040007-CPR2013-IT

(2/2)

Declared performance

Essential characteristics	Performance	Technical specification																																																						
Thickness tolerance class	Declared Class T1: Thickness < 50 mm: ±2 mm Thickness 50 - 120 mm: -2/+3 mm Thickness > 120 mm: -2/+6 mm																																																							
Thermal conductivity (λ_D) and Thermal resistance (R_D)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Thickness (mm)</th> <th style="text-align: center;">λ_D: W/mK</th> <th style="text-align: center;">R_D: m²K/W</th> </tr> </thead> <tbody> <tr><td style="text-align: center;">20</td><td style="text-align: center;">0,033</td><td style="text-align: center;">0,60</td></tr> <tr><td style="text-align: center;">30</td><td style="text-align: center;">0,033</td><td style="text-align: center;">0,90</td></tr> <tr><td style="text-align: center;">40</td><td style="text-align: center;">0,033</td><td style="text-align: center;">1,20</td></tr> <tr><td style="text-align: center;">50</td><td style="text-align: center;">0,034</td><td style="text-align: center;">1,45</td></tr> <tr><td style="text-align: center;">60</td><td style="text-align: center;">0,034</td><td style="text-align: center;">1,75</td></tr> <tr><td style="text-align: center;">80</td><td style="text-align: center;">0,035</td><td style="text-align: center;">2,25</td></tr> <tr><td style="text-align: center;">100</td><td style="text-align: center;">0,035</td><td style="text-align: center;">2,85</td></tr> <tr><td style="text-align: center;">120</td><td style="text-align: center;">0,035</td><td style="text-align: center;">3,40</td></tr> <tr><td style="text-align: center;">140</td><td style="text-align: center;">0,037</td><td style="text-align: center;">3,75</td></tr> <tr><td style="text-align: center;">160</td><td style="text-align: center;">0,037</td><td style="text-align: center;">4,30</td></tr> <tr><td style="text-align: center;">180</td><td style="text-align: center;">0,034</td><td style="text-align: center;">5,25</td></tr> <tr><td style="text-align: center;">200</td><td style="text-align: center;">0,035</td><td style="text-align: center;">5,70</td></tr> <tr><td style="text-align: center;">220</td><td style="text-align: center;">0,035</td><td style="text-align: center;">6,25</td></tr> <tr><td style="text-align: center;">240</td><td style="text-align: center;">0,035</td><td style="text-align: center;">6,85</td></tr> <tr><td style="text-align: center;">260</td><td style="text-align: center;">0,035</td><td style="text-align: center;">7,40</td></tr> <tr><td style="text-align: center;">280</td><td style="text-align: center;">0,035</td><td style="text-align: center;">8,00</td></tr> <tr><td style="text-align: center;">300</td><td style="text-align: center;">0,035</td><td style="text-align: center;">8,55</td></tr> </tbody> </table>	Thickness (mm)	λ_D : W/mK	R_D : m ² K/W	20	0,033	0,60	30	0,033	0,90	40	0,033	1,20	50	0,034	1,45	60	0,034	1,75	80	0,035	2,25	100	0,035	2,85	120	0,035	3,40	140	0,037	3,75	160	0,037	4,30	180	0,034	5,25	200	0,035	5,70	220	0,035	6,25	240	0,035	6,85	260	0,035	7,40	280	0,035	8,00	300	0,035	8,55	EN 13164:2012 + A1:2015
Thickness (mm)	λ_D : W/mK	R_D : m ² K/W																																																						
20	0,033	0,60																																																						
30	0,033	0,90																																																						
40	0,033	1,20																																																						
50	0,034	1,45																																																						
60	0,034	1,75																																																						
80	0,035	2,25																																																						
100	0,035	2,85																																																						
120	0,035	3,40																																																						
140	0,037	3,75																																																						
160	0,037	4,30																																																						
180	0,034	5,25																																																						
200	0,035	5,70																																																						
220	0,035	6,25																																																						
240	0,035	6,85																																																						
260	0,035	7,40																																																						
280	0,035	8,00																																																						
300	0,035	8,55																																																						
Compressive strenght	Declared level: CS(10/Y)200 ≥ 200 kPa (thick. 20 mm) Declared level: CS(10/Y)300 ≥ 300 kPa (thick. 30 - 300 mm)																																																							
Dimensional stability under specified conditions	Declared class: DS(70,90) At 70° C and 90% U.R.: Change in size ≤ 5%																																																							
Deformation under specified conditions	Declared class: DLT(2)5 At 70° C, 168 ore, 40 kPa: Change in size ≤ 5%																																																							
Long term water absorption by total immersion (28 days)	Declared level: WL(T)0,7 Absorption ≤ 0,7% vol.																																																							
Long term water absorption by diffusion (28 days)	Declared level: WD(V)5 Absorption ≤ 5% vol. (thick. 20 - 50 mm) Declared level: WD(V)3 Absorption ≤ 3% vol. (thick. 60 - 300 mm)																																																							
Water vapour diffusion resistance factor (μ)	Declared level: MU80 (thick. 20 - 300 mm)																																																							
Freeze-thaw resistance	Declared level: FTCD1 Absorption ≤ 1% vol.																																																							
Reaction to fire	Euroclass E																																																							